

Auto Multiple Choice - Feature # 277: Non-numeric student id

Status:	Closed	Priority:	Normal
Author:	Hiroto Kagotani	Category:	
Created:	06/05/2014	Assignee:	
Updated:	04/12/2018	Due date:	
Description:	Some universities use student ids in the form of e.g. "T14C999". Letters represent student's faculty and department. This is an example usage of a new command for such student ids. <pre> \AMCcode*{studentid}{7}{TC,0-9,0-9,A-C,0-9,0-9,0-9} </pre> Then it will render: <pre> []T []0 []0 []A []0 []0 []0 []C []1 []1 []B []1 []1 []1 []2 []2 []C []2 []2 []2 []3 []3 []3 []3 []3 ... </pre>		

History

10/30/2014 06:52 pm - Christian Delfosse

using a "true" student id takes a lot of vertical space because ten digits are necessary, therefore limiting the number of questions.
with ~100 students, one might have three 5-digit columns, or four 4-digit columns, etc
since everything finally boils up to having a code in a .csv file, the feature could be useful for that purpose too.

10/31/2014 02:30 pm - Alexis Bienvenüe

- Target version set to 1.4.0

10/05/2017 12:34 pm - Alexis Bienvenüe

- Status changed from New to Feedback

The LaTeX command @\AMCcodeGrid@ is coming with revision commit:23df58dff482 for that purpose. You can use for example

```
\AMCcodeGrid[top]{student}{TC,0123456789,0123456789,ABC,0123456789,0123456789,0123456789}
```

Please test!

03/06/2018 09:29 am - Alexis Bienvenüe

- Status changed from Feedback to Closed

- % Done changed from 0 to 100

04/12/2018 01:28 pm - Hiroto Kagotani

This feature perfectly works.

Thanks!