

Auto Multiple Choice - Bug # 56: Choices in tabular environment

Status:	Closed	Priority:	Normal
Author:	Hiroto Kagotani	Category:	
Created:	05/02/2012	Assignee:	
Updated:	05/07/2012	Due date:	
Description:	I want to align choices on a table using tabular environment. But when I create the following question, I get error messages from AMC: Answer number ID used several times for the same question: 1 ... <pre><pre> \begin{questionmult}{table}\AMCnoCompleteMulti Answer this question. \begin{choicescustom}[o] \begin{tabular}{ p{5cm} p{5cm} } \hline \wrongchoice{wrong 1} & \correctchoice{correct 2} \\ \hline \correctchoice{correct 3} & \wrongchoice{wrong 4} \\ \hline \end{tabular} \end{choicescustom} \end{questionmult} </pre></pre>		

History

05/02/2012 06:38 am - Hiroto Kagotani

I simply added \global to counter increments.

Is that correct?

```
<pre>
--- automultiplechoice.sty.orig 2012-05-02 10:55:07.000000000 +0900
+++ automultiplechoice.sty      2012-05-02 13:39:48.000000000 +0900
@@ -485,12 +485,12 @@
\def\AMCbeginAnswer{}
\def\AMCanswer#1#2{#1 #2}
\def\AMCendAnswer{}
-\newcommand{\correctchoice}[2][\advance\AMCrep@count\@ne\relax%
+\newcommand{\correctchoice}[2][\global\advance\AMCrep@count\@ne\relax%
  \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:B]^^J}\fi%
  \global\AMCune@bonnettrue%
  \AMCload@@@reponse\une@rep{\ifAMC@correc\AMC@marque{#1}{1}%
    \else\AMC@marque{#1}{\fi}{#2}}{\the\AMCrep@count}\ignorespaces}
-\newcommand{\wrongchoice}[2][\advance\AMCrep@count\@ne\relax%
+\newcommand{\wrongchoice}[2][\global\advance\AMCrep@count\@ne\relax%
  \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:M]^^J}\fi%
  \AMCload@@@reponse\une@rep{\AMC@marque{#1}{\fi}{#2}}{\the\AMCrep@count}%
  \ignorespaces}
</pre>
```

05/02/2012 08:47 am - Alexis Bienvenüe

Yes, I think there is no drawback.

05/07/2012 05:15 pm - Hiroto Kagotani

Committed as revision r1046.

05/07/2012 07:55 pm - Alexis Bienvenüe

- *Status changed from New to Closed*